

ECOSPHERE



Zinc Free Floor Finish

An environmentally preferable Zinc-free floor seal and finish formulated with the most advanced polymer technology. Meets today's need for a product that contains no zinc or other heavy metals that can be harmful to wastewater treatment systems. This low odor finish has exceptional durability and flexibility and can be maintained with scrub and recoat procedures, spray buffing or high speed burnishing. Can be used to protect synthetic floors.



ENVIRONMENTALLY RESPONSIBLE COMPARISON

Traditional Products	ECOSPHERE
Zinc cross-linked acrylic and modified-acrylic emulsion polymer	None
Formaldehyde	None
	Zinc-free cross-linked polymers
	1,2-benzisothiazoline-3-one
Traditional Compound Descriptions:	ECOSPHERE Compound Descriptions:
<p>Zinc cross-linked acrylic and modified-acrylic emulsion polymer – is used as a binder in floor finish and sealers. Trace amount of zinc may cause problems with toxicity of sewage effluent and meeting discharge permit requirement.</p> <p>Formaldehyde – is commonly used as a preservative in coatings as well as detergents. However, it is a suspect carcinogen.</p>	<p>Zinc-free cross-linked polymers – is used as a binder in floor finish and sealers. It reduces toxicity of sewage effluent.</p> <p>1,2-benzisothiazoline-3-one – is an efficient microbiostat preservative for aqueous compositions such as floor finish and sealers. Low corrosivity and low odor. It is not suspected carcinogens.</p>

PRODUCT SPECIFICATIONS

Non-volatile Solids:	20.0 ± 0.5%	Buffability:	Spray buffing or high speed burnishing
Color:	Milky emulsion	Removability:	With instant type strippers
Odor:	Low	Detergent Resistance:	Excellent
pH:	8.0 – 9.0	VOC Content:	0.34 lbs./gal.
Dry/Recoat Time:	45 minutes min.	Storage/Stability:	1 year
Slip Resistance:	0.5 min. by ASTM-D2047	Weight Per Gallon:	8.50 lbs./gal.
Durability:	Excellent	Freeze/Thaw Stability:	Keep from freezing