MATERIAL SAFETY DATA SHEET Kandel and Son, Inc.

SECTION I: PRODUCT INFORMATION			
Product Name or	Kandel & Son Odor Control Aerosol 6.75 oz aerosol container.	Manufactured For:	Kandel and Son., Inc. 211 Park Avenue Hicksville, NY 11801 (516)-931-4455
Emergency Telephone No.	1-888-564-3204		
Chemical Names and Synonyms	Odor Eliminator	Chemical Family	Solvent
Dot Shipping Name	Aerosol	Hazard Class	

SECTION 2 – HAZARDOUS INGREDIENTS / FORMULA			
Formula		Vapor Pressure Weight %	
	Acetone (67-64-1)	181 mm Hg @ 68F 71	
	Propane (74-98-6)	6350 mm Hg(a) 68F = 18	
	Butane (106-97-8)	1640 mm Hg $\widetilde{@}$ 68F 8	
	Fragrance (N/A)		
HMIS Ratings	Health=1, Flammability = 4,	Reactivity = 0	

SECTION 3 – PHYSICAL CHEMNICAL CHARACTERISTICS			
BOILING POINT (F $^{\mathrm{O}}$)	> -44 ^O		
SPECIFIC GRAVITY (H20=1)	0.70	рН	-
VAPOR PRESSURE (mm Hg)	Heavier than air	PERCENT VOLATILE VOL (%)	N/A
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE	Slower than ether
		(Butyl Acetate = 1)	
SOLUBILITY IN WATER	NIL	APPEARANCE AND ODOR	Aerosol spray

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA			
FLASH POINT (METHOD	-156 ⁰ F	FLAMMABLE LIMITS	Lower 1.9 Upper 13.0
USED)			
EXTINGUISHING MEDIA	Foam, CO2, Dry Chemical, Fog		
SPECIAL FIRE FIGHTING	Water may be ineffective. Water may be used to cool container to prevent pressure		
PROCEDURES	buildup and explosion when exposed to extreme heat. If water is used, fog nozzles are		
	preferred. Wear goggles and self-contained breathing apparatus.		
FIRE AND EXPLOSION	Closed containers may explode from internal pressure buildup when exposed to		
HAZARDS	extreme heat and discharge contents. Vapor accumulation can flash or explode if		
	ignited. Overexposure to decomposition products may cause a health hazard.		
	Symptoms may not be readily apparent. Obtain medical attention.		

SECTION 5 - HEALTH HAZARD DATA			
INHALATION	Respiratory irritation, headache, nausea, fatigue, drowsiness, impaired coordination		
SKIN / EYE CONTACT	Skin: Contact may dry the skin. Prolonged contact may cause moderate irritation.		
	Eyes: Liquid or vapor may cause moderate to severe irritation.		
SKIN ABSORPTION	Not easily absorbed. Solvent action can dry the skin causing skin to crack, leading to		
	dermatitis.		
INGESTION	Not a likely route of exposure. If swallowed, seek immediate medical assistance.		
GENERAL HEALTH HAZARDS	ACUTE: Eye irritant. Possible skin irritant. CHRONIC: None known		
CARCINOGENICITYFLASH	N/A	NTP CARCINOGEN	No
POINT (METHOD USED)			
IARC MONOGRAPHS	No	OSHA REGULATED	No
MEDICAL CONDITIONS GENERALLY AGRIVATED BY EXPOSURE None known		None known	
EMERGENCY FIRST AID	Inhalation: Move to fresh air. Administer oxygen if needed. Apply artificial		
PROCEDURES	respiration if breathing has stopped. Get medical attention.		
	Skin: Wipe off excess. Wash with soap and water. Seek medical attention if irritation		
	persists.		
	Eyes: Flush with plenty of water. Remove contact lenses and flush again. Seek		
	medical attention.		

SECTION 6 – REACTIVITY DATA			
STABILITY	Stable	CONDITIONS TO AVOID	Application to hot surfaces. Storage
			above 120F. Exposure to open flame.
INCOMPATIBILITY -	Strong Oxidizing Ag	HAZARDOUS DECOMPOSI	May produce fumes when heated to
MATERIALS TO AVOID		PRODUCTS	decomposition
HAZARDOUS	None known		
POLYMERIZATION			

SECTION 7 – PRECAUTIONS FOR SAFE HANDLING AND USE		
IN CASE OF SPILLS	Avoid breathing vapors. Ventilate area. Remove all sources of ignition. Clean area with	
	absorbent material and place in closed containers for disposal.	
WASTE DISPOSAL METHOD	Dispose of in accordance with local, state and federal regulations. Before attempting	
	cleanup, refer to other section of this MSDS for hazard caution information.	
PRECAUTIONS IN HANDLING		
AND STORAGE	baway from heat, sparks, and flame. Do not store at temperatures above 120° F. Do not	
	puncture cans. Do not incinerate or burn cans. Do not stick pins, nails or other sharp	
	objects into opening on top of can. Do not spray in eyes.	
OTHER PRECAUTIONS	Use with adequate ventilation. To prevent vapor build-up open doors and windows or	
	use an explosion proofs exhaust fan to ensure fresh air exchange during and after use.	
	Do not breath vapor, gas, or spray mist. When using, do not eat, drink, or smoke. Avoid	
	contact with eyes, skin, and clothing. Wear protective equipment. Wash hands	
	thoroughly after handling. Remove contaminated clothing and wash before reuse.	
	Empty containers may retain product residues. Follow label warnings even after can is	
	empty. Do not store in basements.	

SECTION 8 – SPECIAL PROTECTION INFORMATION		
RESPIRATORY PROTECTION	Avoid breathing vapors. Use with adequate ventilation equal to out of doors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapors. In confined areas, use approved air line type respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.	
EXHAUST AND VENTILATION		
	ventilation in volume to keep PEL/TLV of most hazardous ingredients below acceptable	
	limits and LEL below stated limit.	
GLOVES AND EYE PROTECT	Wear solvent-resistant gloves if exposure is prolonged or frequent.	
EYE PROTECTION	Safety glasses are recommended.	
OTHER PROITECTIVE EQUIP	Solvent resistant aprons are recommended when handling large quantities of this	
	formula.	
WORK / HYGENIC PRACTICE	Eye wash and safety showers in the workplace are recommend.	